HG268 Smart gloss meter

- 3.5-inch color display for easy viewing
- Multiple sets of measurement data can be displayed at the same time, Easy to compare
- Connect to PC, more extend functions
- Super configuration of hardware, integrated multiple innovative technologies
- Built-in lithium ion rechargeable battery with long lifespan





HG series economic gloss meter is independently developed by 3nh ,with independent intellectual property ,manufactured according to ISO2813 and GB/T 9754. HG series with characteristic of larger display screen ,supply with high-end QC software ,stable performance ,high accuracy and easy to use .

> Gloss measurement so easy with one-touch to complete!





PRODUCT FEATURES

1.20, 60 and 85° in one: from high to low gloss – have the specified angle on hand

- 2. Concise appearance, feel good
- 3.Display 5 sets of measurement data, good for comparison
- 4.Built-in lithium ion rechargeable battery
- 5.Basic model measurement can meet basic glossiness testing requirements
- 6.Connect to PC, more extend functions
- 7.One button for all angles measurement at the same location
- 8.Comply with international standards
- 9.Stable performance, easy to read data.
- 10.Optional accessories: micro printer; Easy to carry, without computer can be continuously printed out the measurement of various parameters, easy to save.





APPLICABLE INDUSTRIES



SPECIFICATION FEATURES

Measuring Angle:20°/60°/85°

Comply with standard: ISO 2813, GB/T 9754, ASTM D 523, ASTM D 2457

Measuring Area (mm):20°: 10x10 60°: 9x15 85°: 5x36 Measuring Range:20°:0~2000GU 60°:0~1000GU 85°:0~160GU

Division Value:0.1GU

Measurement Range:0-10GU 10-100GU 100-2000GU Repeatability: ± 0.1GU $\pm 0.2 GU$ ± 0.2%GU **Reproducibility:** ± 0.2GU $\pm 0.5 GU$ $\pm 0.5\% GU$

Measurement Standard: Conform with JJG696 first class glossmeter

working requirement

Chromaticity Corresponding: Corresponding with CIE 1931(2°) under CIE C light source

Errors: ±1.5, ±1.5% Measuring Time: 1.0s Dimension:L*W*H:160mm*75mm*90mm

Weight:350g

Language: Chinese/English Battery: 3200mAh Li-ion Battery

Display:TFT 3.5 inch Interface: USB

Storage: Basic mode: 1000;

Software: GQC6 Quality Control Software with QC report printing functions and

more extended functions.

Operation Temperature:0~40°C(32~104°F) Storage Temperature:-20~50°C(-4~122°F)

Humidity: <85% relative humidity, no condensation

Standard Accessories: Power Adapter, USB cable, User Manual, CD (Including QC

software), Calibration Plate

Optional Accessories:Miniature Printer

GUANGDONG THREENH TECHNOLOGY CO., LTD.



Spectrophotometers



Colorimeters



Haze Meters



Gloss Meters









Light Booths Test Charts

★CONTACT US





(☑) Email:3nh@3nh.com



Add: 6-8th floors, Building B33, Low Carbon Headquarters Park, Xincheng Road No.400, Zengcheng District, Guangzhou, Guangdong Province, China